Nice

large columns

Нурро 7000

For swing gates with leaves up to 3 m, ideal for





Electromechanical gear motor, surface mounted, also in 24 Vdc version with magnetic encoder, with articulated arm.

Single model for right and left leaves.

Two irreversible versions, with 230 Vac (HY7005) and 24 Vdc (HY7024) power supplies with magnetic encoder. Easy and quick to install: thanks to fewer connections and nothing welded to the gates.

Pre-wired, incorporated double limit-switch both during opening and closing (HY7005).

Long-lasting: solid metal mechanics.

Compact: shockproof bodywork with no sharp corners. Recommended control units: Moonclever MC800 for HY7005: Moonclever MC824H for HY7024.

24 Vdc version with magnetic encoder. Perfect for intensive use, compatible with the control unit Moonclever MC824H:

- · simple programming, by means of a single key:
- · automatic memorization of limit switches on opening and closing with self-learning function;
- · automatic fault diagnostics;
- · programming of pause time:
- · pedestrian pass door:
- · deceleration on opening and closing:
- · obstacle detection with dual technology:
- · operation in event of power failure by means of optional rechargeable batteries (PS324);
- · provision for connection of latest generation resistive sensitive edges.

Nice BiDirectional products indicate the status of the automations and confirm correct reception of the command.

Discover the complete range of BiDirectional products on page 176.

Yubii is the new Nice ecosystem that connects all the automations in the home.

Discover all the benefits of the Yubii system on page


Die-cast, aluminium, key-operated unlock system, complete with protected key. Designed to accommodate external release, too Sturdy, anti-shearing arm, galvanised and painted; strengthened in those areas subjected to greater mechanical stress

DIMENSIONS

UTILISATION LIMITS








A Standard arm - B Arm with accessory

The shape, the height of the gate and the weather conditions can considerably reduce the values shown in the graph to the side.

Use in windy areas 230 Vac models.







CORE Nice Wi-Fi-Radio Gateway.

Pc./Pack 1



IBT4N Interface for connecting the O-View program-

ming unit. Pc./Pack 1



BIDI-ZWAVE Plug-in communication interface between

Z-Wave™ gateways and Nice motors.

Pc./Pack 1



IT4WIFI

Smart Wi-fi interface to manage gates and garage doors by smartphone (*).

Pc./Pack 1



HYA12 Longer articulated arm (see the layout).

Pc./Pack 1



PLA₁₀ Vertical 12 V electric lock.

Pc./Pack 1

Signboard.

Pc./Pack 1



PLA11 Horizontal 12 V electric

lock.

Pc./Pack 1



KIO

Key-operated selector switch for low voltage contacts, with release mechanism for metal cord.

Pc./Pack 1

ACCESSORY FOR 24 V VERSION



6 m cable release kit

for KIO.

Pc./Pack 1

KA1

PS324 24 V battery with integrated battery charger.

Pc./Pack 1



SOLEMYO KIT The solar power to

automate gates, garage doors or barrier gates.

See page 229.

TECHNICAL SPECIFICATIONS

Code	Description	Pack/Pallet
HY7024	Irreversible, 24 Vdc, with magnetic encoder, with shear-proof articulated arm, galvanized and painted	16
HY7005	Irreversible, 230 Vac, with sturdy articulated shear-proof arm, galvanized and painted, with limit switch on opening and closing	16

Code	HY7024	HY7005									
ELECTRICAL DATA											
Power supply (Vac 50 Hz)*	-	230									
Power supply (Vdc)	24	-									
Absorption (A)	5	1,2									
Power (W)	120	258									
PERFORMANCE DATA											
Speed (rpm)	2	1,7									
Torque (Nm)	250	400									
Work cycle (%)	80	30									
DIMENSIONAL AND GENERAL DATA											
Protection level (IP)	43										
Working temp. (°C Min/Max)	-20 ÷ +50										
Dimensions (mm)	350x16	350x165x242 h									
Weight (kg)	1	13									

^{* 60} Hz version available on request.

COMPATIBILITY TABLE WITH CONTROL SYSTEMS AND ACCESSORIES

		control unit/receiver							transmitter							photocells										flashing	
Code	MC200 / Built-in*	MC800 / CKIBD / OXILR	DPR0500/ OKIBD / OXILR	DPROS24/ OXIBD / OXILR	MC424L / Built-in* / 0x8BD / 0x1LR	MC824H / CKIBD / OXILR	MC824HR / Oxibd / Oxilr	ERA INTI	ERA ONE	ERA ONE BD	ERA ONE LR	ERA FLOR	NICEWAY	BPS	BPM	ER.	EPS8	BFMB	EPL8	EPM0W	F210	FT210	F2108	FT210B	BLAC	BLDC	WLT
HY7024						•		•	•	•	•		•				•	•	•	•			•			•	•
HY7005		•						•	•	•	•	•	•	•	•	•					•	•			•		

^{*} Radio receiver incompatible with Opera system