

KIT PRODUCT TECHNICAL DATASHEET

SET R23/374



Composition SET R23/374

CODE	DESCRIPTION	QTY
R23/371	Electromechanical articulated motor 230V AC, irreversible, ideal for swing gates with leaf up to 3.5 m with mechanical limit switch, without arms. Complete with fixing plates.	2
LT303	Arms long for articulated motor.	2
KIT H70/22	Electronic kit with control unit H70/200AC for 2 motors, with T80/TX2 remote control.	1
Composition KIT H70/22		
	H70/200AC/BOX Control unit for 2 motors 230V AC with slow-down functions, in plastic box.	1
	H93/RX22A/I Plug-in receiver fixed code 2 channels 433,92 MHz (500 storable codes) for control units series H70, B70, EDGE, CTRL and F70.	1
	T80/TX2 Dual code transmitter (modality fixed code or rolling code), 433,92 MHz, 2 channels, with copy function.	2
	R90/F2ES Pair of external photocells synchronized.	1
	FIFTHY/230 LED flashing light 230V - 115V with integrated antenna.	1
	R99/C/001 Signboard "Automatic Opening".	1

PRODUCT TECHNICAL SPECIFICATIONS

Power line supply	230V AC - 50Hz
Stand-by consumption	0,5W
Motor power supply	230V AC
Power rating	200W
Frequency of use	50%
Torque	400 N m
Operating temperature	-20+55° C
Protection level	IP44

Reductor Type	Irreversible
Manoeuvre speed	1,5 Rpm
Opening time	14 s
Motor thermal protection	150° C
Incorporated condenser	10 µF
Limit switch	Microswitch in opening and closing
Encoder	-
Maximum dimension product in mm (L x W x H)	355 x 190 x 160
Product weight packed (Kg)	35,2

PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION

